

■ Two-stage high-power heater.



QUICK-HEAT SOLDERING IRONS TQ-77/95



Power monitor lamp



trigger



TQ-77

SPECIFICATIONS

Model	TQ-77	TQ-95
Voltage	110-130 V, 220-240 V AC 50/ 60 Hz	
Power Consumption	High 150 W / Low 15 W (110-130 V model) High 200 W / Low 20 W (220-240 V model)	
Insulation Resistance	Over 100 MΩ (500 V DC)	
Heater	Ceramic Heater	
Power Cord Length	1.5 m	
Length	167 mm	210 mm
Weight	90 g	65 g
Accessories	Soldering Iron Tip (TQ-77RT-B)	Soldering Iron Tip (TQ-77RT-B) Cap for TQ-95 (TQ-CAP)

*The length does not include the cord bushing. The weight does not include the cord.

NOTE: High power runs while trigger/quick button is pressed.

POWER LAMP (TQ-77 ONLY)

Easy heater-on check

COMFORTABLE SOLDERING

High-power ceramic heater

TWO-STAGE HEAT-SWITCH SYSTEM

10 times higher power than normal

ERGONOMIC GRIP

Prevents fatigue



TQ-95




QUICK-HEAT BUTTON
Controls power

Specially processed
long-life tip

Heat-resistant cap for quick
storage after use.

REPLACEMENT TIPS

TQ-77RT-SB (110-130V)	TQ-77RT-B (110-130V)	TQ-77RT-BC (110-130V)
TQ-77RT-SB-L (220-240V)	TQ-77RT-B-L (220-240V)	TQ-77RT-BC-L (220-240V)
TQ-77RT-2C (110-130V)	TQ-77RT-3C (110-130V)	
TQ-77RT-2C-L (220-240V)	TQ-77RT-3C-L (220-240V)	



() Size for 220-240 V AC model